



## AUTOMATIC MOLDBOARD PLOUGH

Thanks to the special absorber spring mechanism installed in each body, it is easy to get rid of all kinds of obstacles in the stoned areas and the plough is prevented from mechanical damages by this way. The hardness adjustment of the special shock absorber springs is available.

Model	Number of Furrows	Length	Width	Height	Working Depth	Working Width	Space Between Furrows	Weight	Required Power
		mm	mm	mm	mm	inch	cm	kg	Hp
AG-AMP 12	2	2075	1150	1450	210-300	12-14-16	75	420	50-70
	3	2825	1485	1450	210-300	12-14-16	75	630	60-75
	4	3575	1880	1490	260-330	12-14-16	80	810	75-90
	5	4375	2085	1550	260-330	12-14-16	80	920	90-120
	6	5175	2335	1550	260-330	12-14-16	80	1070	110-130
AG-AMP 14	2	2105	1215	1450	250-350	12-14-16	85	450	60-70
	3	2955	1545	1450	250-350	12-14-16	85	860	75-90
	4	3805	1955	1450	250-350	12-14-16	85	840	90-120
	5	4655	2150	1490	250-350	12-14-16	85	950	110-130
	6	5505	2400	1550	250-350	12-14-16	85	1115	110-130
AG-AMP 16	2	2235	1270	1550	300-450	12-14-16-18	90	480	60-75
	3	3135	1600	1450	300-450	12-14-16-18	90	690	60-90
	4	4035	2015	1450	300-450	12-14-16-18	90	870	90-120
	5	4935	2210	1490	300-450	12-14-16-18	90	980	120-150
	6	5835	2465	1550	300-450	12-14-16-18	90	1155	120-180
AG-AMP 20	2	2335	1370	1500	300-450	12-14-16-18	90-95	520	60-90
	3	3285	1700	1500	300-450	12-14-16-18	90-95	730	60-90
	4	4235	2115	1540	300-450	12-14-16-18	90-95-100	910	90-120
	5	5185	2310	1600	300-450	12-14-16-18	90-95-100	1020	120-150
	6	6135	2565	1600	300-450	12-14-16-18	90-95-100	1195	120-180

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.