



RIDGER PLOUGH

Opportunity to open several furrows in one pass. Adjustable furrow width and dike height. Your new assistant for irrigation systems. Depth control tyre optional.

| Model | Number of Furrows | Clearance | Distance Between Furrows | Ditch Bottom Width | Ditch Width | Ditch Depth | Weight | Required Power |
|------------------------|-------------------|-----------|------------------------------|--------------------|-------------|-------------|--------|----------------|
| | | cm | cm | cm | cm | cm | kg | Hp |
| AG-RPW 3 Bracket Frame | 3 | 60 | 60-95 (within 5 cm interval) | 25 | 34-40-46 | 20-35 | 224 | 40-55 |
| AG-RPW 4 Bracket Frame | 4 | 60 | 60-95 (within 5 cm interval) | 25 | 34-40-46 | 20-35 | 285 | 55-65 |
| AG-RPW 5 Bracket Frame | 5 | 60 | 60-95 (within 5 cm interval) | 25 | 34-40-46 | 20-35 | 355 | 65-80 |
| AG-RPW 3 Profile Frame | 3 | 65 | 70-90 | 25 | 34-40-46 | 20-35 | 262 | 50-60 |
| AG-RPW 4 Profile Frame | 4 | 65 | 70-90 | 25 | 34-40-46 | 20-35 | 363 | 60-80 |
| AG-RPW 5 Profile Frame | 5 | 65 | 70-90 | 25 | 34-40-46 | 20-35 | 423 | 80-90 |

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.