



SUBSOILER

The tires allow to adjust the depth at the desired level and also allow each leg to reach the same depth at the same time. Thanks to the shaped leg made of 15mm plat, it performs the function of both plow and bottom deep exploder of the soil. Model AG-SS which is manufactured as 2, 4, 6, 8, 10 legs is suitable for the use of the tractors ranged between 70 and 260 horsepower.

Model	Number of Tines	Distance Between Tines	Main Frame Dimensions	Length	Height	Width	Working Width	Weight	Required Power
	pcs	cm	cm	cm	cm	cm	cm	kg	hp
AG-SS 2	2	50	120x120x8	130	170	160	140	520	70-80
AG-SS 4	4	50	120x120x8	160	170	250	230	835	100-120
AG-SS 6	6	50	120x120x8	190	170	350	330	1573	160-180
AG-SS 8	8	50	120x120x8	220	170	450	430	2400	200-240
AG-SS 10	10	50	120x120x8	250	170	550	530	3050	240-260
AG-SS 12	12	50	120x120x8	280	170	650	630	3755	300-350
AG-SS 2 With Roller	2	50	120x120x8	180	170	160	140	1001	70-80
AG-SS 4 With Roller	4	50	120x120x8	210	170	250	230	1175	100-120
AG-SS 6 With Roller	6	50	120x120x8	240	170	350	330	1785	160-180
AG-SS 8 With Roller	8	50	120x120x8	260	170	450	430	2650	200-240
AG-SS 10 With Roller	10	50	120x120x8	300	170	550	530	3920	240-260
AG-SS 12 With Roller	12	50	120x120x8	330	170	650	630	4500	300-350

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.